1. THE MOWING OPERATION IS A SPECIAL OPERATION. IT SHALL BE SCHEDULED AND COMPLETED DURING DAYLIGHT WORK SHIFTS. THE WORK SHALL BE SUSPENDED DURING PERIODS F POOR VISIBILITY.

2. TRACTOR MOWERS SHALL HAVE AN AMBER BEACON OPERATING AT ALL TIMES. IF IT IS NECESSARY FOR THE MOWER TO ENCROACH ONTO THE TRAVEL LANE, THE MOWER SHALL BE FOLLOWED BY A PROTECTIVE VEHICLE WITH OPERATING FLASHING LIGHTS (SEE 619-025).

3. APPROVED PERSONAL PROTECTIVE EQUIPMENT (PPE) SHALL BE WORN WHILE ON TRACTORS NOT EQUIPPED WITH AN ENCLOSED CAB. PPE IS REQUIRED WHEN EXITING TRACTOR WITHIN RIGHT OF WAY.






TABLE 024-01: REQUIRED SIGN SIZES	
SIGN	FREEWAY
W21-8	48×48
WARNING FLAG	18×18



Department of Transportation

U.S. CUSTOMARY STANDARD SHEET

WORK ZONE TRAFFIC CONTROL FREEWAY WORK BEYOND SHOULDER MOWING OPERATION

APPROVED DECEMBER 2, 2021

Robert Limoges ROBERT LIMOGES, P.E. DIRECTOR, OTSM

619-024

ISSUED UNDER EI 21-028

ALL MOWERS SHALL BE EQUIPPED WITH A SLOW MOVING VEHICLE PLACARD AND 2 (18"MIN.) SQUARE ORANGE FLAGS 500 FT. (MINIMUM) (13 SKIP LINES) AND 2 MILE (MAXIMUM) (20 REFERENCE MARKERS) MOWING AHEAD SIGN SHALL BE PLACED ON A TEMPORARY SIGN STAND AND SHALL BE LOCATED ON THE SIDE OF THE ROADWAY WHERE THE MOWING OPERATION IS OCCURRING AND SHALL BE MOVED PERIODICALLY SO THAT IT IS KEPT AS CLOSE AS PRACTICAL TO THE ACTUAL LOCATION OF THE MOWER. IF PROTECTIVE VEHICLE IS REQUIRED TO MOVE THE SIGN, USE 619-025.

DATE/TIME = 06-DEC-2021 14:55 USER = oboatwright